

Tuya Smart Bluetooth Access Control Reader



H2-BT

Tuya Smart Bluetooth Access Control Reader

The H2-BT is a Bluetooth-enabled waterproof touch keypad + RFID access controller. It's integrated with Tuya which supports 100 users(including 255 card/PIN users). It's available for both iOS and Andrdroid.

Specifications

User Capacity	Hardware User: 1000, APP User: 100	Relay	One (NO, NC, Common)
Common User	988	Adjustable Relay Output Time	0-99 Seconds
Visitor User	10	Lock Output Load	2 Amp Maximum
Panic User	2	Wiegand Interface	EM card version: Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits)
PIN Length	4~6 digits		Mifare card version: Wiegand 26~44 bits, 56bits, 58bits input & output (Factory default: Wiegand 34bits)
Operating Voltage	12~18V DC	PIN Output	4 bits, 8bits (ASCII), 10 digits Virtual Number (Factory default: 4bits)
Idle Current	<= 60mA	Environment	Meets IP66
Active Current	<=150mA	Operating Temperature	-40 C ~ 60 C (-40°F ~ 140°F)
Proximity Card Reader	EM or Mifare	Operating Humidity	0%RH ~ 98%RH
Radio Technlogy	125KHz/13.56MHz	Physical	Zinc-Alloy
Read Range	2~6cm	Color	Sliver & Black
Wiring Connections	Relay output, exit button, alarm, door contact, Wiegand input/output	Dimensions	L149 x W70 x H25 (mm)

